

Declaration of Performance

In accordance with Regulation (EU) No 305/2011, as amended by the UK Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and 2020

1. Unique product-type reference:

Magply Magnesium Oxysulphate Board.

2. Type:

Self-supporting composite lightweight panels of 3,6,9,12,18 & 20mm thickness.

3. Intended use:

For use in external walls, claddings, internal walls, ceilings, flooring, roofing, and recovery board applications.

4. Manufacturer:

Name

IPP Limited

Address

Bradwell Hall,

Essex, CM0 7HX

- 5. Authorised Representative: N/A
- 6. System or systems of AVCP: System 3
- 7. In case of the declaration of performance concerning a construction product covered by a designated standard:

British Board of Agrément, UK Approved body number 0836

Issued UKTA-0836-23/6858

- 8. N/A
- 9. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Fire resistance	Euroclass A1 (Non-combustible)	BS EN 13501-1: 2007
Thermal conductivity (λ)	0.19 W/mK	BS EN 12667: 2001
Pull-through strength (Axial loading test with drywall screws)	1195N (9mm) 1415N (12mm)	ETAG 006:2000/ Amended: 2012
Racking strength	5.08 kN/m (9mm)	BS EN 1995-1-1: 2004
Resistance to moisture	Category B	BS EN 12467: 2012
Dimensional tolerance	Level 1	BS EN 12467: 2012
Resistance to mould	Resistant	BS 3900-G6: 1989
Impact resistance – soft body Impact resistance – hard body	9mm – Category I & II 9 & 12mm – Cat. I & II	EOTA TR001:2003, §2 EOTA TR001:2003, §3

10. The performance of the product identified above is in conformity with the declared performance identified in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer as identified above.

Signed for and on behalf of the manufacturer by:

G.M.Pirret. Director

Place and date of issue:

Essex UK 16 October 2023

Signature: