



PIR INSULATION - DECLARATION OF PERFORMANCE

DOP Number: 004/20

Designation Code: PIR-EN 13165- T2-W2-L2-DS(TH)4-DS(-20)2-WL(T)2-CS(10/Y)150

1. Unique Identification code of Product type

Therm Floor / MF - Insulated Foil Faced Underfloor Board

2. Type, Batch or Serial Number or any other Element allowing identification of the Product

Under Floor Board 20-200mm

3. Intended use or uses of the product, in accordance with the applicable harmonized technical specification

PIR Thermal Insulation board for the construction Industry

4. Name and registered address of manufacturer

Mannok Insulation Ltd,
Scotchtown, Ballyconnell,
Co Cavan, Ireland

5. System or systems and verification of constancy of performance of the product as set out in AVCP System 3

6. Covered by harmonised standard

EN 13165

7. Name and address of the notified bodies determining product-type on the basis of type testing

BRE Global, Bucknalls Lane,
Watford, Herts, WD259XX, UK

British Board of Agrément,
PO Box 195, Bucknalls Lane,
Garston, Herts WD2598A, UK

LGAI Tech centre S.A./ Applus
Campus UAB, Apto Correos 08193
Bellaterra, Spain
Notified body no. 0370

8. In case of the Declaration of Performance concerning a construction product for which a European Technical Assessment has been issued

Not applicable



9. Declared Performances

Essential Characteristic	Performance		Harmonised Technical Specification
Reaction to Fire	Euro Class E		All Thicknesses
Thermal Resistance	RD ((m ² .K)/W)		d ^N 25mm = 1.14 d ^N 30mm = 1.36 d ^N 50mm = 2.27 d ^N 55 mm = 2.5 d ^N 60mm = 2.73 d ^N 70 mm = 3.18 d ^N 80 mm = 3.64 d ^N 90 mm = 4.09 d ^N 100mm = 4.55 d ^N 110mm = 5 d ^N 120 mm = 5.45 d ^N 125 mm = 5.68 d ^N 130mm = 5.91 d ^N 140 mm = 6.36 d ^N 150mm = 6.82 d ^N 200mm = 9.09
Thermal Conductivity	W/mK		0.022
Compressive Strength	kPa		CS (10\Y)150
Long Term Water Absorption			WL (T) 2
Length & Width	mm	1200 x 2400	L2&W2 <1000 mm: ± 4mm 1000 to 2000mm: ± 5mm 2001 to 4000mm: ± 8mm >4000mm: ± 12mm
PIR Thickness	d ^N		20mm – 200mm T ₂
Squareness	mm/m		S _b ≤/ = 5
Flatness	mm		Length ≤ 2.50m Area ≤ 0.75m ² : deviation ≤ 5mm Area > 0.75m ² : deviation ≤ 10mm
Release of Dangerous substances	No harmonised test method available		
Flexural Strength	No performance declared.		
Tensile Strength Perpendicular to Faces	No performance declared.		
Durability of reaction to fire against heat, weathering, aging/ degradation	Reaction to Fire does not change over time		
Dimensional stability under specified temperature and humidity conditions	DS(TH)4 & DS(-20,-)2		

EN 13165

10. The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Name and position held by the person empowered to sign the declaration on behalf of the manufacturer.

Liam McCaffrey CEO
16th November 2020