

HadleySPEC WARRANTED SYSTEM

# Technical Product Datasheet

Item Code: 5305

# **HADLEY 52mm Track**

Hadley Tracks (U Channels) are cold-rolled steel Tracks used mainly at the head and base junctions of Hadley Drylining System to create non-loadbearing internal partitions.

Manufactured in accordance with EN 14195:2005











Scan QR code for Hadley Drylining *Golden Thread*Documents: Technical Datasheet, Material Safety
Datasheet, Declaration of Performance (DoP), O&M
Manual and more...



## **Product Information**



Width	52mm
Flange	25mm
Gauge	0.55mm
Lengths	3m
Pack Quantities	10 / 50 / 200 / 1000

#### **REACTION TO FIRE:**

Δ1

#### YIELD STRENGTH:

210 (N/mm2)

#### SERVICE CUT OUTS:

N/A

#### SYSTEM PERFORMANCE INFORMATION:

To be installed as a part of a complete Hadley Drywall system to achieve both Fire and Acoustic performance. To understand more about our fully warranted and tested solutions, please contact our Hadley Technical Support Team.

#### STORAGE & HANDLING:

When installing Hadley components please ensure full PPE is used and the site is practicing a safe working environment alongside industry standards.

#### DISPOSAL:

Hadley Metal is fully recyclable.

#### SYSTEMS USED:

HadleySOLO – Single Stud System

HadleyHUSH- Single Stud with Resilient Bar System

HadleyDUO - Twin Frame I Stud System

HadleySHAFT - Shaftwall System

HadleyBRACE – Twin Framed braced C Stud System

Technical Product Datasheet

HadleySPEC WARRANTED SYSTEM

Item Code: 581B

# **HADLEY 62mm Track**

Hadley Tracks (U Channels) are cold-rolled steel Tracks used mainly at the head and base junctions of Hadley Drylining System to create non-loadbearing internal partitions.

Manufactured in accordance with EN 14195:2005











Scan QR code for Hadley Drylining Golden Thread
Documents: Technical Datasheet, Material Safety
Datasheet, Declaration of Performance (DoP), O&M
Manual and more...



## **Product Information**



Width	62mm
Flange	25mm
Gauge	0.55mm
Lengths	3m
Pack Quantities	10 / 100 / 300

### REACTION TO FIRE:

Δ1

#### YIELD STRENGTH:

210 (N/mm2)

#### SERVICE CUT OUTS:

N/A

#### SYSTEM PERFORMANCE INFORMATION:

To be installed as a part of a complete Hadley Drywall system to achieve both Fire and Acoustic performance. To understand more about our fully warranted and tested solutions, please contact our Hadley Technical Support Team.

#### STORAGE & HANDLING:

When installing Hadley components please ensure full PPE is used and the site is practicing a safe working environment alongside industry standards.

#### DISPOSAL:

Hadley Metal is fully recyclable.

#### SYSTEMS USED:

HadleySOLO - Single Stud System

HadleyHUSH- Single Stud with Resilient Bar System

HadleyDUO - Twin Frame I Stud System

HadleySHAFT - Shaftwall System

HadleyBRACE – Twin Framed braced C Stud System



HadleySPEC WARRANTED SYSTEM

# Technical Product Datasheet

Item Code: 5307

# **HADLEY 72mm Track**

Hadley Tracks (U Channels) are cold-rolled steel Tracks used mainly at the head and base junctions of Hadley Drylining System to create non-loadbearing internal partitions.

Manufactured in accordance with EN 14195:2005











Scan QR code for Hadley Drylining Golden Thread
Documents: Technical Datasheet, Material Safety
Datasheet, Declaration of Performance (DoP), O&M
Manual and more...



## **Product Information**



Width	72mm
Flange	25mm
Gauge	0.55mm
Lengths	3m
Pack Quantities	10 / 50 / 300 / 600

#### **REACTION TO FIRE:**

Δ1

#### YIELD STRENGTH:

210 (N/mm2)

#### SERVICE CUT OUTS:

N/A

#### SYSTEM PERFORMANCE INFORMATION:

To be installed as a part of a complete Hadley Drywall system to achieve both Fire and Acoustic performance. To understand more about our fully warranted and tested solutions, please contact our Hadley Technical Support Team.

#### STORAGE & HANDLING:

When installing Hadley components please ensure full PPE is used and the site is practicing a safe working environment alongside industry standards.

#### DISPOSAL:

Hadley Metal is fully recyclable.

#### SYSTEMS USED:

HadleySOLO – Single Stud System

HadleyHUSH- Single Stud with Resilient Bar System

HadleyDUO - Twin Frame I Stud System

HadleySHAFT - Shaftwall System

HadleyBRACE – Twin Framed braced C Stud System



Technical Product Datasheet

HadleySPEC WARRANTED SYSTEM

Item Code: 5309

# **HADLEY 94mm Track**

Hadley Tracks (U Channels) are cold-rolled steel Tracks used mainly at the head and base junctions of Hadley Drylining System to create non-loadbearing internal partitions.

Manufactured in accordance with EN 14195:2005











Scan QR code for Hadley Drylining *Golden Thread*Documents: Technical Datasheet, Material Safety
Datasheet, Declaration of Performance (DoP), O&M
Manual and more...



## **Product Information**



Width	94mm
Flange	25mm
Gauge	0.55mm
Lengths	3m
Pack Quantities	10 / 50 / 300

#### **REACTION TO FIRE:**

Δ1

#### YIELD STRENGTH:

210 (N/mm2)

#### SERVICE CUT OUTS:

N/A

#### SYSTEM PERFORMANCE INFORMATION:

To be installed as a part of a complete Hadley Drywall system to achieve both Fire and Acoustic performance. To understand more about our fully warranted and tested solutions, please contact our Hadley Technical Support Team.

#### STORAGE & HANDLING:

When installing Hadley components please ensure full PPE is used and the site is practicing a safe working environment alongside industry standards.

#### DISPOSAL:

Hadley Metal is fully recyclable.

#### SYSTEMS USED:

HadleySOLO - Single Stud System

HadleyHUSH- Single Stud with Resilient Bar System

HadleyDUO - Twin Frame I Stud System

HadleySHAFT - Shaftwall System

HadleyBRACE – Twin Framed braced C Stud System

## Technical Product Datasheet

HadleySPEC WARRANTED SYSTEM

Item Code: 5310B

# **HADLEY 148mm Track**

Hadley Tracks (U Channels) are cold-rolled steel Tracks used mainly at the head and base junctions of Hadley Drylining System to create non-loadbearing internal partitions.

Manufactured in accordance with EN 14195:2005











Scan QR code for Hadley Drylining Golden Thread
Documents: Technical Datasheet, Material Safety
Datasheet, Declaration of Performance (DoP), O&M
Manual and more...



## **Product Information**



Width	148mm
Flange	25mm
Gauge	0.55mm
Lengths	3m
Pack Quantities	10 / 80 / 160

#### **REACTION TO FIRE:**

A1

#### YIELD STRENGTH:

210 (N/mm2)

#### SERVICE CUT OUTS:

N/A

#### SYSTEM PERFORMANCE INFORMATION:

To be installed as a part of a complete Hadley Drywall system to achieve both Fire and Acoustic performance. To understand more about our fully warranted and tested solutions, please contact our Hadley Technical Support Team.

#### STORAGE & HANDLING:

When installing Hadley components please ensure full PPE is used and the site is practicing a safe working environment alongside industry standards.

#### DISPOSAL:

Hadley Metal is fully recyclable.

#### SYSTEMS USED:

HadleySOLO - Single Stud System

HadleyHUSH- Single Stud with Resilient Bar System

HadleyDUO - Twin Frame I Stud System

HadleySHAFT - Shaftwall System

HadleyBRACE – Twin Framed braced C Stud System