

OPTIM-R®

Product safety information

These products are articles not intended to release substances and do not contain substances of very high concern and as such are exempt from the requirements of REACH Regulation (EU) 2020/878.

1 Identification of the product and of the company / undertaking

1.1 Product Identifier

Kingspan OPTIM-R®.

1.2 Relevant identified uses of the product

Flat roofing application and flooring

1.3 Details of the supplier of the Product Safety Information Sheet

Company Name: Kingspan Insulation Limited

Company Address: Pembridge, Leominster, Herefordshire, HR6 9LA, UK.

Tel: +44 (0) 1544 388 601

Fax: +44 (0) 1544 388 888

Email: info@kingspaninsulation.co.uk

Website: www.kingspaninsulation.co.uk

1.4 Emergency Telephone Number

Tel: +44 (0) 1544 387 382

Email: technical@kingspaninsulation.co.uk

2 Hazards Identification

2.1 Classification

There are no known hazards associated with the normal handling or use of this insulation product.

2.2 Other hazards

Care should be taken to avoid puncturing or rupture of the outer barrier film. In case of rupture and exposure of the core, please refer to Sections 6 and 8 of this sheet.

Exposure of the panels to very high temperatures may result in the emission of smoke and decomposition / combustion of products.

3 Composition information

The core of Kingspan OPTIM-R® contains no respirable fibres and therefore falls outside the scope of European Community Directive Amendment 97/69/EC.

Core: Encapsulated in polyester non-woven fabric and covered with a multi-layered barrier film.

4 First aid measures

4.1 Description of first aid measures

Inhalation: Possible irritation or soreness in throat and nose. Remove affected person to fresh air.

Skin: Temporary irritation or rash. Rinse affected areas with water.

Eyes: Temporary irritation or inflammation. Flush immediately with copious amounts of water. Do not rub eyes.

Ingestion: No information available.

Other: Seek medical attention if discomfort persists.

5 Firefighting measures

5.1 Extinguishing media

Suitable media: Water spray (fog), foam, CO₂ or dry chemical.

Unsuitable media: Not applicable.

5.2 Special hazards arising from the product

It is prudent to take precautions against ignition, fire spread and combustion products. Do not inhale fumes.

5.3 Advice for firefighters

Firefighters should use self-contained breathing apparatus and saturate burning foam with water from a spray nozzle. Dust is classified as weakly explosive (St. Class 1).

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

In the event of rupture of the outer layers and exposure of the core material, any powder released should be cleaned up by a method that avoids / minimises the creation of airborne dust. In the event of high dust levels, use approved respiratory protective equipment (see Section 8).

Amorphous silica has a drying action on skin. Dust produced from the Kingspan OPTIM-R® core may, like any other dust, aggravate pre-existing upper respiratory and lung diseases.

6.2 Reference to other sections

See section 8 for PPE.
See section 13 for Disposal considerations.

7 Handling and storage

7.1 Precautions for safe handling

The Kingspan OPTIM-R® panels should not be cut or penetrated. The substrate must be clean, dry and level, and free of sharp objects or edges.

8 Exposure controls / personal protection

8.1 Control Parameters

In the event of rupture of the envelope, the core contents of amorphous silica, silicon carbide and polyester fibres may be released. Note the following workplace exposure limits for these materials:

Workplace exposure limits

Great Britain

EH40/2005 Workplace exposure limits, as amended. Published by the Health and Safety Executive, UK.

Substance	Long-term exposure limit (8-hr TWA reference period)	
	Inhalable dust (mg.m ⁻³)	Respirable dust (mg.m ⁻³)
Amorphous Silica	6.0	2.4
Silicon Carbide	10.0	4.0

Germany

German "List of MAK and BAT Values 1998" for maximum concentrations at the workplace.

Substance	Long-term exposure limit (8-hr TWA reference period)	
	Inhalable dust (mg.m ⁻³)	Respirable dust (mg.m ⁻³)
Amorphous Silica	4.0	N/A
Silicon Carbide	N/A	1.5

8.2 Exposure Controls

Respiratory protection:	Approved, properly fitting, respirators with the appropriate nominal protection factor.
Hand protection:	Gloves, moisturising or barrier creams may prevent the drying of the skin in contact with silica dust.
Eye protection:	Goggles or safety glasses with side shields. When installing a product with reflective facings in very bright or sunny weather it is advisable to wear UV protective sunglasses or goggles.
Skin protection:	Overalls that are loose fitting at the neck and the wrist. When installing a product with reflective facings in bright sunlight, it is advisable to consider skin protection from UV.
Other:	The products are non-load bearing. Access and work should not be carried out on unsupported boards.

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Silver or white foil covered panels
Odour:	None.
pH:	Not applicable.
Melting point:	Not applicable.
Flash point:	Not applicable.
Insulation density:	Typically 180-210 kg/m ³ .
Solubility in water:	Not applicable.
Auto-ignition temperature:	(Envelope materials) 355 °C
Oxidising properties:	Not applicable.
Other data:	None.

9.2 Other information

No additional chemical or physical properties to report.

10 Stability and reactivity

The plastic materials used to encapsulate Kingspan OPTIM-R® cores and as reinforcing filaments will begin to decompose at approximately 150 °C. The thermal decomposition of products will vary with temperature and oxygen availability but could include oxides of carbon.

11 Toxicological Information

11.1 Information on toxicological effects

There are no known health effects arising from handling or using Kingspan OPTIM-R® insulation as supplied.

11.2 Information on other hazards

No additional information available.

12 Ecological information

12.1 Toxicity

Kingspan OPTIM-R® cores are manufactured using inert materials that remain stable over a considerable time. No eco-toxicological studies exist for these products.

13 Disposal considerations

13.1 Waste treatment methods

Waste insulation is non-hazardous.

Generally, Kingspan OPTIM-R® cores may be disposed of at a normal landfill site that has been licensed for industrial waste. It is prudent to ensure that the panels are appropriately bagged and sealed prior to disposal. The cores may be recycled.

With respect to disposal, observe usual safety precautions.

Clean, undamaged product may be re-used.

Waste product, including packaging, should be disposed of in accordance with the Waste Hierarchy – Reduce, Re-Use, Recycle. Refer to national waste handling legislation.

14 Transport information

Read this section in conjunction with Section 7.

Ensure security of load and where necessary sheeting / roping should be used.

It is recommended that mechanical lifting equipment is used when moving bulk quantities.

15 Regulatory information

15.1 Safety, health and environmental regulations / legislation specific for the product

United Kingdom

The Health and Safety at Work etc. Act 1974.

The Control of Substances Hazardous to Health Regulations.

HSE EH40/05 Workplace Exposure Limits (as Amended 2011).

MDHS 14 General methods for the gravimetric determination of respirable and total inhalable dust.

Germany

Deutsche Forschungsgemeinschaft: MAK und BAT Werte Liste 1998 – Maximale Arbeitsplatzkonzentrationen und Biologische Arbeitsstofftoleranzwerte (List of MAK and BAT Values 1998 – Maximum Concentrations and Biological Tolerance Values at the Workplace).

16 Other information

The information contained here is offered in good faith and is based on our current knowledge.

We thereby withhold the right to update and amend this document as necessary.

The information should not be taken as guarantee of specific performance and users should make their own assessment and make all applicable personnel aware accordingly.

The wearing of appropriate safety equipment is strongly recommended as a precaution and the product should only be used in its design application.

Users should visit the Kingspan Insulation website or contact the Kingspan Insulation Technical Services Department to ensure information is correct.

This data sheet does not constitute a workplace assessment. The information provided represents the state of our knowledge regarding this material at the date of its publication. The information provided does not constitute a product specification and no warranty expressed or implied is hereby made.

The information relates only to the specific material designated when used in applications it has been designed for. This information may not be valid for such material used in combination with any other materials or in any other processes, unless specified in the text.

Contact details

Great Britain

Kingspan Insulation Ltd
Pembroke | Leominster
Herefordshire | HR6 9LA

T: +44 (0) 1544 388 601
E: info@kingspaninsulation.co.uk
www.kingspaninsulation.co.uk

For individual department contact details please visit
www.kingspaninsulation.co.uk/contact

Ireland

Kingspan Insulation Ltd
Castleblayney | County Monaghan

T: +353 (0) 42 979 5000
E: info@kingspaninsulation.ie
www.kingspaninsulation.ie

For individual department contact details please visit
www.kingspaninsulation.com/ie/contact



For the most up-to-date version
of this product safety sheet
please scan or click [here](#).

To access pre-existing product information or information relating to previously sold/discontinued products please email literature@kingspaninsulation.co.uk.

The information contained in this brochure is believed to be correct at the date of publication. Kingspan Insulation Limited ("Kingspan Insulation") reserves the right to alter or amend the product specifications without notice due to continuous improvement commitments. There may also be relevant changes between publications with regard to legislation, or other developments affecting the accuracy of the information contained in this brochure. Product thicknesses shown in this document should not be taken as being available ex-stock and reference should be made to the current Kingspan Insulation price-list or advice sought from Kingspan Insulation's Customer Service Department. The information, technical details and fixing instructions etc. included in this literature are given in good faith and apply to uses described. Kingspan Insulation does not accept responsibility for issues arising from using products in applications different from those described within this brochure or failure to correctly follow the information or instructions as described within this brochure. Recommendations for use should be verified with a suitable expert or professional for suitability and compliance with actual requirements, specifications and any applicable laws and regulations. For other applications or conditions of use, Kingspan Insulation offers a technical advisory service (see above for contact details), the advice of which should be sought for uses of Kingspan Insulation products that are not specifically described herein. Please check that your copy of this literature is current by contacting the Kingspan Insulation Marketing Department.

© Kingspan, OPTIM-R and the Lion Device are Registered Trademarks of the Kingspan Group plc in the UK, Ireland and other countries. All rights reserved.

Registered in England & Wales, No. 01882722. Registered Office: Pembroke, Leominster, Herefordshire HR6 9LA UK. VAT GB428602456.

Registered in Ireland, No. 54621. Registered Office: Bree Industrial Estate, Castleblayney, Co. Monaghan, Ireland. VAT IE45750691.

