

Multi Acoustic Roll.

April 2024 | Data Sheet



Description.

Superglass Multi Acoustic Roll is a non-combustible glass mineral wool insulation roll. The flexible roll is partially perforated at 2x600mm and 3x400mm widths to allow quick and easy installation between common stud/joist spacings, minimising gaps at joints and reducing on-site cutting.

Application.

Superglass Multi Acoustic Roll is designed to provide thermal and acoustic insulation for the following applications:

- Internal walls and floors
- Separating walls and floors
- Timber and metal stud partitions
- Drylining system

Performance.

Density:

Manufactured at a minimum density of 10kg/m³.

Thermal Conductivity:

Declared thermal conductivity (lambda (λ) value) of 0.044W/mK.

Fire Classification:

Deemed non-combustible with a fire classification of Euroclass A1 (the highest possible rating) when tested to BS EN 13501-1 Reaction to Fire.



Typical applications:
Internal walls and floors.



Acoustic
Insulation



Thermal
Insulation



Non-
combustible



Easy to
Install



Recycled
Content

Intelligent Environments
Superglass

superglass.co.uk

Multi Acoustic Roll.

Technical Characteristics.

Product Specification.

Thickness (mm)	Length (m)	Width (mm)	Pack Area (m ²)	Packs per pallet	Thermal Conductivity (W/mK)	Thermal Resistance (m ² K/W)	Product Code
60	11.25	1200/2x600/3x400	13.500	24	0.044	1.35	2144295
75	10.50	1200/2x600/3x400	12.600	24	0.044	1.70	2144388
80	10.40	1200/2x600/3x400	12.480	24	0.044	1.80	2144296
100	10.10	1200/2x600/3x400	12.120	24	0.044	2.25	2144294

Please note that all dimensions are nominal.

Additional Information.

Vapour Resistivity.

The product has a nominal vapour resistivity of 5 MNs/gm.

Environmental credentials.

- ISO 14001 - Environmental Management Systems (EMS) certified. Certificate number: EMS 646508
- Contains no ozone-depleting substances or greenhouse gases. For more information, please refer to the Environmental Product Declaration (EPD).
- Manufactured from up to 84% recycled glass.
- Generic BRE Green Guide Rating of A+.

Standards and Approvals.

Manufactured in accordance with:

- BS EN 13162:2012(+A1:2015) Thermal insulation products for buildings - Factory made mineral wool (MW) products.
- BS EN 13172: 2012 Thermal insulation products - Evaluation of conformity.
- BS EN ISO 9001 - Quality Management Systems (QMS). Certificate number: FM 02264.

Certifications.

- UKCA certified to BS EN 13162:2012+A1:2015. Certificate number: 0086 CPR 469699.
- CE marked to EN 13162:2012+A1:2015. Certificate number: 0751-CPR-399.0-01.

A copy of the product Declaration of Performance (DoP) can be downloaded from the Superglass website.

Handling & Storage.

Due to its physical characteristics, Multi Acoustic Roll is quick and easy to handle and install.

The product is supplied compression packed in polythene to provide short term protection only. For long term protection, the product must be stored indoors, or under a waterproof covering and off the ground to protect from weather damage. The product should not be left permanently exposed to the elements.

All Superglass products are non-hygroscopic, will not rot, degrade, or sustain vermin and will not encourage the growth of mould, bacteria, or fungi.

Intelligent Environments
Superglass

**UK
CA**

CE

bsi. ISO 14001:2015
Environmental
Management

bsi. ISO 9001
Quality
Management

BRE Global
Verified
EPD

**MADE IN
BRITAIN**

NBS Source
Manufacturer Partner

Superglass Insulation Ltd | Thistle Industrial Estate | Kerse Road | Stirling | FK7 7QQ | UK

MAR02

Technical

Hotline: 0808 1645 134

Email: technical.stirling@etexgroup.com

Customer Services

Tel: 01786 451170

Email: customerservice.stirling@etexgroup.com

Social

✕ [superglassinsulationuk](https://www.superglassinsulationuk.com)

in [superglassuk/](https://www.superglassuk.com)

f [superglass_uk](https://www.superglass_uk.com)

[superglass.co.uk](https://www.superglass.co.uk)

All rights are reserved, including those of photomechanical reproduction and storage in electronic media. Commercial use of the processes and work activities presented in this document is not permitted. Extreme caution was observed when putting together the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of errors pointed out.

etex inspiring ways
of living