

Technical Product Datasheet

HadleySPEC WARRANTED SYSTEM

Item Code: 5299

HADLEY 70mm C STUDS

Hadley C Studs are cold-rolled steel studs used as part of a Hadley Drylining System to create non-loadbearing internal partitions.

Manufactured in accordance with EN 14195:2005













Scan QR code for Hadley Drylining Golden Thread
Documents: Technical Datasheet, Material Safety
Datasheet, Declaration of Performance (DoP), O&M
Manual and more...



Product Information



REACTION TO FIRE:

YIELD STRENGTH: 210 (N/mm2)

SERVICE CUT OUTS:

80mm x 30mm @ 600mm Centres

SYSTEM PERFORMANCE INFORMATION:

To be installed as a part of a complete Hadley Drywall system to achieve both Fire and Acoustic performance. To understand more about our fully warranted and tested solutions, please contact our Hadley Technical Support Team.

Width	70mm
Flange	32mm/34mm
Gauge	0.55mm
Lengths	2.4m / 2.7m / 3.0m / 3.6m / 4.2m
Pack Quantities	10 / 50 / 300

STORAGE & HANDLING:

When installing Hadley components please ensure full PPE is used and the site is practicing a safe working environment alongside industry standards.

DISPOSAL:

Hadley Metal is fully recyclable.

SYSTEMS USED:

HadleySOLO - Single Stud System

HadleyDUO – Twin Frame I Stud System (*used only at abutments)

HadleyBRACE – Braced Twin Frame System

HadleyHUSH – Single Stud System using Resilient Bars

HadleySTAGGER – Staggered Stud System (*used only at abutments)

HadleyLINE- Independent I Stud Lining System (*used only at abutments)