

HadleySPEC WARRANTED SYSTEM

Technical Product Datasheet

Item Code : 5954C

HADLEY 92mm I STUDS

Hadley I Studs are cold-rolled steel studs used as part of a Hadley Drylining System to create non-loadbearing internal partitions.

Manufactured in accordance with EN 14195:2005






Scan QR code for Hadley Drylining *Golden Thread* Documents: Technical Datasheet, Material Safety Datasheet, Declaration of Performance (DoP), O&M Manual and more...



Product Information



REACTION TO FIRE: A1

YIELD STRENGTH:

210 (N/mm2)

SERVICE CUT OUTS:

75mm x 38mm @ 600mm Centres

SYSTEM PERFORMANCE INFORMATION:

To be installed as a part of a complete Hadley Drywall system to achieve both Fire and Acoustic performance. To understand more about our fully warranted and tested solutions, please contact our Hadley Technical Support Team.

Width	92mm
Flange	38mm
Gauge	0.90mm
Lengths	3m / 3.6m / 4.2m / 5m / 6m
Pack Quantities	5 / 50

STORAGE & HANDLING:

When installing Hadley components please ensure full PPE is used and the site is practicing a safe working environment alongside industry standards.

DISPOSAL:

Hadley Metal is fully recyclable.

SYSTEMS USED:

HadleySOLO – Single Stud System HadleyDUO – Twin Frame I Stud System HadleySHAFT – Shaftwall System HadleyLINE – I Stud Lining System HadleySTAGGER – Staggered Stud System