



## Acoustic Partition Roll

ODE Acoustic Partition Roll is a glass mineral wool roll designed to be installed in internal wall and floor applications to provide excellent levels of sound absorption and noise reduction.


The 1200mm wide roll is pre-cut at 600mm to allow a simple friction fit between studs.



### Key Performances and Benefits

Reaction to Fire classification	A1 non-combustible to EN 13501-1
Sound absorption co-efficient	0.8- 1.0
BREEAM	A+ rating according to BRE Green Guide
Recycled content	Manufactured from >80% recycled glass
Easy installation	No tear, low wastage, simple friction fit
Long Life	Does not degrade, decompose, or become mouldy over time

## Acoustic Performance



- 1- U Profile
- 2- Insulation Material
- 3- Plaster Board
- 4- C Profile

Profile Thickness	Plaster Board	Starflex APR	Plaster Board	Wall Thickness	Sound Absorption Value With Insulation
mm	mm	mm	mm	mm	dB
50	12.5	50	12.5	75	40.1
75	15	80	15	105	44.2
100	15	100	15	130	45.1

## Specifications

Thickness mm	Density Kg/m <sup>3</sup>	Length M	Width mm	M2 Per Pack	Packs Per Palet
25	24	20	1200 (2x600)	24	24
50	18	10	1200 (2x600)	12	32
65	15	9	1200 (2x600)	10.8	24
75	15	8	1200 (2x600)	9.6	24
100	12	6.5	1200 (2x600)	7.8	32

## Hyperpack Palletized Packaging

Thanks to the hyperpack packaging system, ODE Lunaflex glass wool facilitates:

- Loading more product per volume
- Loading and unloading using transpallet
- Minimum stocking cost
- Can be stored outdoors



More information and certification documents at [www.ode.com.tr/en](http://www.ode.com.tr/en)

ISO 27001 | ISO 9001 | ISO 14001 | ISO 50001 | ISO 45001

